ALL DIMENSION IN mm

ND.	QTY.	DESCRIPTION	ASTM WCB	ASTM S.S.304	ASTM S.S.316		
1	1	B□DY	A-216 Gr.WCB	A-351 Gr.CF8	A-351 Gr.CF8M		
2	1	CAP/COVER	A-216 Gr.WCB	A-351 Gr.CF8	A-351 Gr.CF8M		
3	1	SCREEN	SS-304 PERFOR	ATED 40 MESH	SS-316 PERFORATED 40 MESH		
4	1	GASKET	S.S.316 SPIRAL WOUND WITH GRAPHOIL FILLER				
5	Req.	NUT&BOLT	A-194 GR.2H/193 GR.B7	A-194 GR.B8/193 GR.8	A-194 GR.B8M/193 GR.8M		

* FLANGE FACING & DRILLING DIM. ACCORDING TO 150# & F/F ACCORDING TO 150#

DIMENSIONAL DETAILS


ALL DIMENSION ARE IN mm

SIZ	SIZE INCH MM		ØΒ	ØD	К	RF	F	øJ	Т	N
INCH										
1″	25	127	25	110	79.2	51	1.6	16	11.2	4
1-1/2"	40	165	38	125	98.6	73	1.6	16	14.2	4
2"	50	203	51	150	120.7	92	1.6	19	15.8	4
2-1/2"	65	216	64	180	139.7	105	1.6	19	17.5	4
3″	80	241	76	190	152.4	127	1.6	19	19	4
4"	100	292	102	230	190.5	157	1.6	19	23.8	8
5 <i>"</i>	125	356	127	255	215.9	186	1.6	22	23.8	8
6"	150	406	152	280	241.3	216	1.6	22	25.4	8
8″	200	495	203	345	298.5	270	1.6	22	28.5	8
10"	250	622	254	405	362	324	1.6	25.4	30.2	12
12"	300	698	305	485	431.8	381	1.6	25.4	31.8	12

TEST PRESSURE

RE STANDARD

HYDRAULIC TEST-ANSI 150# BDDY : 32Kg/Cm²g MFG. & DESIGN : MLT
INSP. & TESTING : 150#
Face to Face : 150#
End Connection : F/E TO B 16.5 150# R.F.





L-82, G.I.D.C. Estate, Nr. Water tank Odhav AHMEDABAD - 382415

DRN. : VASUDEV	'Y' TYPE STRAINER 150#					
CHD. :	FLANGED ENDS, 25MM to 300MM					
APD. :	PRESSURE RATING - ANSI 150 #					
APD, :						
SCALE : NTS						
DATE :						
	DRG.ND,:- STR / 150 / 25 to 300 / G.D.					